

APPLICATION FOR STREET OPENING PERMIT

The undersigned hereby makes application for a permit to open:

_____, for the purpose of _____

Type of pavement to be cut:

- CONCRETE OIL AND CHIP ASPHALT GRAVEL OTHER

AS A CONDITION OF THIS APPLICATION, THE UNDERSIGNED AGREES:

1. THE ONE TRAFFIC Lane will be open at all times, unless excavation is required for the full pavement width.
2. To replace the pavement under the direction and guidelines of the Street Department and to deposit the sum as required by City Ordinance to insure such replacement. Deposit, less \$50.00 will be refunded at the end of 90 days after pavement replacement and final approval of the Street Superintendent of City Engineer, if the excavation has been properly filled and pavement replaced. In the event that the excavation has not been properly filled and/or replaced, the City has the right to apply any portion of the remaining Deposit towards to cost of properly filling or replacement of the pavement. The City has the right to file civil action against the applicant to recover unreimbursed expenses, court costs and attorney's fees.
3. Applicant shall provide all required barricades, signage and flagging prior to start of work.
4. Applicant shall provide all materials as specified by the Street Department.
5. Applicant agrees to hold and save the city harmless from any claims for damages arising from any cause from said installation or construction. A copy of the excavator's certificate of insured shall be provided with the City named as additional insured, if required.
6. All backfilling of over sewer, water, gas of other utilities in the streets or alleys of Jerseyville shall be done under the following provisions:
Concrete Streets:
 - Concrete shall be sawed a minimum of half the depth of the pavement but not less than 3 inches, before concrete removal.
 - Area to be removed shall be 24 inches past the excavation on all sides of the excavation, and not less than 6 foot width to be replaced.
 - In the event concrete pavement is to be removed for the full width of the street, there shall be no less than 10 feet width of concrete with the trench to be excavated centered in the removed section.
 - Replacement of excavated material shall be with type III backfill (sand of ¾" aggregate). Backfill shall be jetted or mechanically compacted and approved by Street Superintendent or City Engineer prior to placing concrete.
 - Replacement of concrete shall consist of boring #4 bars at 12 inch centers, 4 inch minimum depth into adjacent pavement. Class X concrete (6.4 bag) or approved mix by the City Engineer shall be used. All alternate mix designs shall be submitted and approved prior to start of work.
 - Any variance to the above shall be submitted and approved prior to start of work.Streets other than Concrete:
 - Pavement shall be sawed 18 inches wider than excavation, removed to rock base and patched with approved materials.
 - Excavations deeper than the road base shall be backfilled with type III backfill (sand or ¾" aggregate.). Backfill shall be jetted or mechanically compacted and approved by Street Superintendent or City Engineer.
 - Patch material shall be at minimum the depth of the adjacent pavement but no less than 4" thick.
 - Patching material shall be placed in 3" maximum thickness and mechanically compacted between each layer placed.

Applicant Signature

____/____/_____
Date

Permit Fee \$ _____